

Ultra SpillPallet Plus Models

Combine High-Strength And Low-Profile Features While Meeting EPA Container Storage Regulations

- Nearly 50% lower than standard spill pallets, drum handling is safer and less strenuous.
- Available in 1-drum, 2-drum and 4-drum configurations.
- Removable grates feature a non-slip surface.



ULTRA-SPILLPALLET PLUS MODELS

Ultra-SpillPallet P1 Plus		Ultra-SpillPallet P2 Plus		Ultra-SpillPallet P4 Plus	
Part# 9606: no drain	Part# 9607: with drain	Part# 9610: no drain	Part# 9611: with drain	Part# 9630: no drain	Part# 9631: with drain
Dimensions: 1016 x 1016 x 304 mm	Weight: 23 kg	Dimensions: 1663 x 1016 x 222 mm	Weight: 39 kg	Dimensions: 1574 x 1574 x 222 mm	Weight: 56 kg
Uniformly Distributed Load: 362 kg	Containment Capacity: 234 litres	Uniformly Distributed Load: 2041 kg	Containment Capacity: 249 litres	Uniformly Distributed Load: 4082 kg	Containment Capacity: 283 litres

Options Available: Polyethylene Loading Ramp (see specifications on page 13), PullOver Covers

U.S. Patent No. 5,615,608

Ultra SpillPallet Fluorinated Models

ULTRA-SPILLPALLET FLUORINATED MODELS

Ultra-SpillPallet P4 Fluorinated	Ultra-SpillPallet P2 Fluorinated
Part# 1210: no drain Part# 1211: with drain	Part# 1212: no drain Part# 1213: with drain
Dimensions: 1346 x 1346 x 298 mm	Dimensions: 1346 x 736 x 419 mm
Weight: 38 kg	Weight: 28 kg
Uniformly Distributed Load: 2721 kg	Uniformly Distributed Load: 1360 kg
Containment Capacity: 249 litres	Containment Capacity: 249 litres
Optional PullOver Covers, Part# 1006	Optional PullOver Covers, Part# 1016

U.S. Patent No. 5,615,608



Certain chlorinated solvents are considered incompatible with standard polyethylene. However, a gas treatment process known as fluorination alters the surface of molded polyethylene products, making them compatible with these and many other aggressive chemicals. The light blue color indicates that the SpillPallets and grates have been fluorinated.